





CB3 UN-Box

1200 x 1000 x 740 mm / 610



Transponder (RFID)



Art.-Nr.: 83281519

Technical data			
Dimensions L x W x H (mm)	1200X1000X765		
Weight(kg)	43.8 kg		
Volume (I)	610		
Material* ²	PE		
Load capacity (kg)* ³	Stacking Load 5000 kg	Holding Capacity 700 kg	Dynamic Load ³ 1200 kg

Characteristics Options

Manufactured in one piece

Runners: 3, unwelded

With lid and 2 tensioning straps

Stackable

Colour: green

Temperature stability: -30 °C to +40 °C, briefly up to +90 °C

Resistant to most chemicals and cleaning agents

Food-safe. HACCP compliant

Container is based on DIN EN 13626 and DIN EN ISO 12048

The design type complies with the test provisions of the international regulations for packagings for the transport of dangerous goods (packaging groups II and III)

Loading quantities (Pcs / Approximate amount)

Container	Container 20': 37 Container 40': –	Container 40' High Cube: 100 Conventional trailer 45' high cube container: 98
-----------	--	--



Labelling

 $Customised\ printing\ and\ numbering\ available\ on\ request\ depending\ on\ quantity.\ Position\ upon\ consultation.$









- *1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.